



Long Life Coolant Red

High quality 40% pre-mixed
(Silicate and Borate Free Japanese Technology)

MATERIAL CODE: EMA1801

Long Life Coolant Red is 40% Pre-Mixed, Silicate & Borate Free Japanese technology ready to use coolant. This is top performance environmentally sensitive, corrosion inhibitor and Anti-Freeze Coolant. This unique Japanese Technology ready to use Antifreeze Coolant offers exceptional performance and engine protection for longest intervals. The selective long -lasting inhibitors technology provides long-term protection of the cooling systems of Gasoline, light and heavy -duty engines, outboard engines and high temperature aluminium engine blocks. Specially designed to withstand the severe demands of long -life coolant laid down by Japanese OEMs. Extremely low depletion rate of the coolant offers long term corrosion protection under all operating conditions.

❖ **SPECIAL FEATURES**

- **Silicate and Borate Free Japanese Technology Ready to use coolant**
- Top performance, environmentally sensitive coolant, anti-Freeze and Corrosion Inhibitor.
- Selective long-lasting inhibitors technology provides long term protection of the cooling system.
- Specially designed to withstand the severe demands of long-life coolant laid down by Japanese OEMs.

❖ **PACK SIZE**

1L, 4L, 208L

❖ **APPLICATIONS.**

Suitable for Gasoline, light-heavy duty, outboard engines and high temperature aluminium engine blocks.

❖ **TYPICAL PROPERTIES**

Glycol Concentrate	40%
Appearance	Red
Density (20°C), g/cm ³	1.066
pH @ 25°C	7.40
Foaming Characteristic ml	0
Freezing Point, °C	-24.5

Note: The Typical Properties may be changed without notice.



Handling Precautions

▼ Follow these precautions when handling this product.

! CAUTION Handling Precautions	<ul style="list-style-type: none">● <u>Inflammation can occur if oil enters the eyes.</u> When handling this oil, wear <u>protective goggles</u> or take other measures to <u>prevent eye contact</u>.● <u>Inflammation can occur if oil comes into contact with skin.</u> When handling this oil, wear <u>protective gloves</u> or take other measures to <u>prevent skin contact</u>.● Do not drink this oil. (Swallowing this oil can cause diarrhea and nausea.)● <u>Keep out of reach of children.</u>● Read the Material Safety Data Sheet (MSDS) for this product before using the product. Obtain the Material Safety Data Sheet from where you purchased the product.
First Aid	<ul style="list-style-type: none">● In case of eye contact, rinse eyes thoroughly with clean water and consult with a physician.● In case of skin contact, wash skin thoroughly with soap and water.● If this oil is swallowed, do not induce vomiting. Consult with a physician immediately.
Disposal of Used Oil and Containers	<ul style="list-style-type: none">● Do not apply pressure to empty containers. The containers may burst if pressure is applied.● Do not weld, heat, drill, or cut the containers. The remaining oil may ignite and the containers may explode.● Follow all applicable laws and regulations when disposing of used oil or containers. If you are unsure of the proper disposal methods, consult first with the seller of the oil.
Storage Method	Seal the container tightly after use in order to prevent dirt, moisture, etc., from entering the oil. Store in a dark location. Avoid direct sunlight.